

SBA TUNER TO IP GETAWAY 080

Compuesto por 8 sintonizadores que demodulan la señal de 8 fuentes y la convierten y empaquetan en TS e IP. La salida IP puede ser configurada a diferentes direcciones y puertos. Soporta TS sobre protocolo UDP. Los 8 canales de entrada pueden estar compuestos por DVB-S/S2/C/T/ISDB-T/ATSC y la salida es TS sobre UDP.



SPECIFICATIONS

- Integrated with demodulation and gateway function.
- Support 8 channels tuner (DVB-S/-S2/-C/-T/ISDB-T/ATSC optional) input and 8 IP output.
- Support MPEG-2 and MPEG-4 TS to IP one way conversion.
- GE output (support parallel 1 Gbps data output channel).
- Support maximum 8 tuner to IP converting channel, the maximum output bit-rate is 800Mbps.
- Support TS over UDP protocol, unicast and multicast.
- Support LCD display and keyboard.
- Support NMS/SNMP management

Interface	Input	8 Channels tuner input (DVB-S/S2/-C/-T/ISDB-T/ATSC optional)
	Output	1 GE output, TS over UDP protocol, unicast and Multicast
Transmission Bit-rate		Maximum total bit-rate is 800Mbps
General	Dimension (WxLxH)	482mm×410mm×44mm
	Weight	3.6kg
	Temperature	0~45°C(working) , -20~80°C(storage)
	Power supply	100~240VAC , 50/60Hz
	consumption	20W

INNER PRINCIPLE

